



POINT MOBILE CO., LTD.
B-9F, Kabul Great Valley, 60-5 Gasan-dong
Geumcheon-gu, Seoul, Korea 153-709
www.pointmobile.co.kr

Model :	Phase :	Originator :	Dept.	Date :
-	-	SW Team	SW	May 26, 2015

SystemSettingClone Instruction

Revision History

Version	Date	Change Description	Remark
1.0	Sep 19, 2014	Initial Draft	

1. Preparation

- 1.1. Format the micro SD card.
- 1.2. Copy PM_SystemSettingClone(v2.x.x).cab, SystemSettingClone.lnk files to \AutoInstall\Cabfile directory of the SD card.
(Please make \AutoInstall\Cabfile folder in SD root)

2. Export

- 2.1. Insert SD card(performed step 1) to terminal.
- 2.2. If you possible, please connect AC adapter, then press and hold Power button for 3 seconds for Reset.



- 2.3. Tap 'SOFT RESET' button.
- 2.4. After reboot, PM_SystemSettingClone(v2.x.x).cab will be Installed automatically and the device will be reboot automatically once again.
- 2.5. Then the SystemSettingClone tool will be run automatically. Tap 'Export' button.



2.6. The device will be export and save to SD card, then reboot automatically.

2.7. Finally, for backup/restore the Wi-Fi settings, the SystemSettingClone is automatically run and terminated after reboot.

3. Import

3.1. **Note: Import step must use same P/N terminal in Step 2 used.**

3.2. Insert SD(performed step 2) card to terminal.

3.3. If you possible, please connect AC adapter, then press and hold Power button for 3 seconds for Reset.



- 3.4. Tap 'SOFT RESET' button.
- 3.5. After reboot, PM_SystemSettingClone(v2.x.x).cab will be Installed automatically and the device will be reboot automatically once again.
- 3.6. The device will be import data from SD card, then reboot automatically.
- 3.7. Finally, for backup/restore the Wi-Fi settings, the SystemSettingClone is automatically run and terminated after reboot.